

Safety data sheet

according to UK REACH Version number 1

Revision: 21.08.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- Trade name: Mipa P 19 E PE-Leichtspachtel
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Knife filler/ Surfacer
- · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: MIPA SE Am Oberen Moos 1 D-84051 Essenbach Tel.: +49 8703 92 20 Fax.: +49 8703 92 21 00 e-mail: sdb-registratur@mipa-paints.com www.mipa-paints.com
- 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

health hazard

H361d Suspected of damaging the unborn child. Repr. 2

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation. Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling: Styrene Maleic anhydride

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Revision: 21.08.2024

Professional Coating Systems

Printing date 21.08.2024

Version number 1

Trade name: Mipa P 19 E PE-Leichtspachtel

	(Contd. of page 1)
2,2'-(m-Tolylimino)	
Reaction mass of (4-methylphenyl)a	2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] mino]-
 Hazard statemen 	ts
H226 Flammable	liquid and vapour.
H315 Causes ski	in irritation.
H319 Causes se	rious eye irritation.
	an allergic skin reaction.
H361d Suspected	of damaging the unborn child.
H372 Causes da	mage to the hearing organs through prolonged or repeated exposure.
· Precautionary sta	atements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235	Store in a well-ventilated place. Keep cool.
· 2.3 Other hazards	
· Results of PBT a	nd vPvB assessment
. DRT: Not applicab	

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

CAS: 100-42-5	Styrene	≥10-≤20%
EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	Flam. Liq. 3, H226; S Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; A cute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 91-99-6 EINECS: 202-114-8	2,2'-(m-Tolylimino)diethanol ♦ STOT RE 2, H373;	≥0.1-<1%
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino] bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]- Eye Dam. 1, H318; () Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	<i>≥</i> 0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	 Maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 % 	<i>≥</i> 0.001-<0.1%



Safety data sheet

according to UK REACH

Version number 1

Revision: 21.08.2024

Trade name: Mipa P 19 E PE-Leichtspachtel

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation. • 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)

GB



Safety data sheet

according to UK REACH

Revision: 21.08.2024

Printing date 21.08.2024

Version number 1

Trade name: Mipa P 19 E PE-Leichtspachtel

(Contd. of page 3)

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

108-31-6 Maleic anhydride

WEL Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ Sen

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

GB

Professional Coating Systems

Printing date 21.08.2024

Safety data sheet

according to UK REACH Version number 1

Revision: 21.08.2024

Trade name: Mipa P 19 E PE-Leichtspachtel

(Contd. of page 4)

- · Breakthrough time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemic	al properties
· General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
• Boiling point or initial boiling point and	Undetermined.
boiling range	145.2 °C (100-42-5 Styrene)
· Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	1.2 Vol % (100-42-5 Styrene)
	8.9 Vol % (100-42-5 Styrene)
· Upper:	31 °C (DIN EN ISO 1523:2002, 100-42-5
· Flash point:	
Auto impition tomporations	Styrene)
• Auto-ignition temperature:	480 °C (DIN 51794, 100-42-5 Styrene)
• Decomposition temperature:	Not determined.
· pH	Not determined.
Viscosity:	
· Kinematic viscosity	Not determined.
Dynamic at 20 °C:	85,000-95,000 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
 Vapour pressure at 20 °C: 	6 hPa (100-42-5 Styrene)
 Vapour pressure at 50 °C: 	35 hPa
Density and/or relative density	
· Density at 20 °C:	1.486 g/cm³ (DIN EN ISO 2811-1)
[.] Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health	
and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
· Solvent content:	enpresive ainvapour mintures are possible.
· VOC (EC)	1.21 %
· Solids content (weight-%):	80.5 %
Sonus content (weight-/0).	
	(Contd. on page 6)
	GB



Safety data sheet

according to UK REACH Version number 1

Revision: 21.08.2024

		(Contd. of page
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Reproductive toxicity Suspected of damaging the unborn child.
- STOT-repeated exposure

Causes damage to the hearing organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)

GB

Professional Coating Systems

Printing date 21.08.2024

Safety data sheet

according to UK REACH Version number 1

Revision: 21.08.2024

Trade name: Mipa P 19 E PE-Leichtspachtel

(Contd. of page 6)

· 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport informat	tion
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN3269
 14.2 UN proper shipping name ADR IMDG, IATA 	UN3269 POLYESTER RESIN KIT POLYESTER RESIN KIT
· 14.3 Transport hazard class(es)	
ADR	
· Class	3 (F3) Flammable liquids.
·Label	3
· IMDG, IATA	
Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	///
· 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Hazard identification number (Kemler of the second sec	Warning: Flammable liquids. code): -
	(Contd. on pa





Safety data sheet

according to UK REACH Version number 1

Revision: 21.08.2024

Trade name: Mipa P 19 E PE-Leichtspachtel	
-------------------------------------------	--

	(Contd. of page 7
EMS Number:	F-E,S-D
· Stowage Category	A
· 14.7 Maritime transport in bulk ac	cording to
IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	3
Tunnel restriction code	E
·IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

· Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- May be fatal if swallowed and enters airways. H304
- Causes severe skin burns and eye damage. H314
- H315 Causes skin irritation.

(Contd. on page 9)

GB

Safety data sheet according to UK REACH

Revision: 21.08.2024

ſ pg Professional Coating Systems

Printing date 21.08.2024

Version number 1

11047	May any an elleverie alie venetien	(Contd. of page 8)
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H361d	Suspected of damaging the unborn child.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H412	Harmful to aquatic life with long lasting effects.	
	Corrosive to the respiratory tract.	
	cation according to Regulation (EC) No 1272/2008	
	sification of the mixture is generally based on the calculation method using	substance data
	g to Regulation (EC) No 1272/2008.	
	ations and acronyms:	
	ord relatif au transport international des marchandises dangereuses par route (European Ag	reement Concerning
	ational Carriage of Dangerous Goods by Road) ernational Maritime Code for Dangerous Goods	
	rnational Air Transport Association	
	pally Harmonised System of Classification and Labelling of Chemicals	
	European Inventory of Existing Commercial Chemical Substances	
	European List of Notified Chemical Substances	
	mical Abstracts Service (division of the American Chemical Society) tile Organic Compounds (USA, EU)	
	istent. Bioaccumulative and Toxic	
	/ Persistent and very Bioaccumulative	
	3: Flammable liquids – Category 3	
	. 4: Acute toxicity – Category 4	
	1B: Skin corrosion/irritation – Category 1B 2: Skin corrosion/irritation – Category 2	
	1: Serious eye damage/eye irritation – Category 1	
	: Serious eye damage/eye irritation – Category 2	
	s. 1: Respiratory sensitisation – Category 1	
	. 1: Skin sensitisation – Category 1	
	. 1A: Skin sensitisation – Category 1A	
	. 1B: Skin sensitisation – Category 1B eproductive toxicity – Category 2	
	3: Specific target organ toxicity (single exposure) – Category 3	
	1: Specific target organ toxicity (repeated exposure) – Category 1	
	2: Specific target organ toxicity (repeated exposure) – Category 2	
	1: Aspiration hazard – Category 1	
Aquatic Cl	hronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	GB -